

SIRIUS

Multi-Purpose Night Vision Monocular

The Armasight Sirius is a high-tech, tough, and durable multi-use Night Vision monocular that delivers great performance at a reasonable cost. Packed with high-tech features, the Sirius is a unit that is equally as appropriate for the hunter as it is for the professional security officer or law enforcement professional. Mission configurable, the Sirius can be hand-held or mounted to a helmet or headgear. It can also be mounted onto a rifle, or used for night photography. Optional lenses can turn it into a long-range night viewing device in seconds.

Despite the low cost, the Sirius features manual brightness control, bright light shut-off circuitry, and a built-in spot/flood IR illuminator. The Armasight Sirius can be equipped with high-performance Gen 2+, including Green phosphor or Armasight's "Quick Silver", which provide users with natural B&W Night Vision displays.

- Compact, rugged design
- Manual Gain control
- Mater and Fog-Resistant
- **Meapon mountable**
- A Head or helmet mountable for hands-free usage
- A Bright light cut-off
- Ergonomic, simple, easy to operate controls
- Outilizes single CR123A lithium battery or AA Alkaline, Adapter included
- Adaptable for use with cameras
- Built-in Infrared illuminator and flood lens
- A Limited two-year warranty













SPECIFICATIONS	
IIT Generation	Gen 2+ SD - "Standard Definition" 45-51 lp/mm Gen 2+ ID - "Improved Definition" 47-54 lp/mm Gen 2+ QS - "Quick Silver" White Phosphor 47-54 lp/mn
Magnification	1x standard (3x, 5x, 7x optional)
Lens System	F/1.2; 24 mm
Field of View	40°
Focus Range	0.25m to infinity
Exit Pupil Diameter	10 mm
Eye Relief	21.5 mm
Diopter Adjustment	-5 to +5 dpt
Manual Gain Control	Yes
Bright Light Cut-off	Yes
Automatic Shut-off System	Yes
Infrared Illuminator	Yes
IR Indicator	Yes
Low Battery Indicator	Yes
Power Supply	CR123 Lithium 3V (1), or AA Alkaline 1.5V (1), or any AA or CR123 type rechargeable batteries with voltage from 1.2V to 3.7V (1)
Battery Life	Up to 60 hours
Environmental Rating	Water and Fog-Resistant
MIL-STD-810	Yes
Operating Temperature	-40° to +50°C (-40° to +122°F)
Storage Temperature	-50° to +70°C (-58° to +158°F)
Overall Dimensions	157 x 60 x 75 mm (6.1 x 2.3 x 2.9 in)
Weight	0.46 kg (1.0 lbs)
Warranty	2 Years
* All data subject to change witho	out notice.







STANDARD COMPONENTS



BATTERY ADAPTOR



OPERATION AND MAINTENANCE MANUAL



CARRYING CASE

OPTIONAL EQUIPMENT







Part No. ANLE7X0017









HELMET MOUNT #4







HELMET MOUNT #183 (SHROUD)



SWING ARM #37



SWING ARM #172



TACTICAL GOGGLE KIT: WILCOX L4 G24















XLR-IR A-FOCAL DOUBLER

